|  | Cass Subdass ISSUE CLASSIFICATION  | U.S. UTILITY POLPE  ACAMMED AM | PAT           | Q .<br>ENT DATE                            |         |
|--|--|--------------------------------|---------------|--|---------|
| [  | APPLICATION NO.   CONT/PRI<br>09/699589  | OR CLASS SUBCLASS              | ART UNIT      | EXAMINER                                   |         |
| APPLICANTS   | Won-Suk Yang<br>Sang-Ho Song<br>Hong-Sik Jeong<br>Ki-Nam Kim<br>Bit line landin  | و و سالتین استورسون            |               | PY H Welss  bit line stud with             |         |
| THE STATE OF THE S | method thereof   | stop layer formed :<br>,       | in void regio | bit line stud with<br>n, and manufacturing |         |
|  |  | 0.493.40                       |               |  | har nga |
|  | and the second of the second o |                                |               |  |         |

The terminal \_\_\_\_\_\_months of this patent have been discialized.

WARNING:

The information disclosed herein may be restricted. Unauthorized disclosure may be pruhibited by the United States Code Title 35, Sections 122, 181 and 368.

Presenting outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

FILED WITH: DISK (CRF) FICHE CD-ROM

ISSUE BATCH NUMBER